



New Item



15443 OB/15443 NBK/15943 OB6



DECORATIVE HAMMERED ROOF PATH LIGHT

Pierced shade sheds decorative patterned light over shrubs or gardens. Coordinates with matching deck light 15063.

SPECIFICATIONS

Housing Pierced brass with brass stem or pieced copper with copper stem

Finish Polished Copper, Olde Brick®, Natural Verdigris, New Brick or Textured Tannery Bronze®

Wiring 35" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt S-8 wedge socket.

Light Bulb 24.4-W. Max. 3156K (15598CLR) (nominal at 12-Volts) supplied. Can also use 18.5-W. 3155K (15599CLR).

Mounting Accessories Included

8" In-ground stake

Optional Mounting Accessories 15601 – Surface Mounting Flange

15607 - Tree/Surface Mounting Bracket

Ordering Guide

15343 OB 12

15343 CO Polished Copper, Copper 15343 OB Olde Brick®, Brass

15943 OB 6 Same as 15343OB. Bulk packed 6 in unbreakable

master with 25' of 16-gauge wire and

Universal Connector for LV Junction. Same as 15343OB. Bulk packed 12

in unbreakable master.

New Brick™, Brass, powder coat 15343NBK

version of Olde Brick®

15343TZT Textured Tannery Bronze®, Brass

15343VG Verdigris, Brass

U.S. Patent No. Des. 408,573

Photometric Light Spread Measurement

from Light 4 Footcandles 8.9 2.8 .15 15443

AND STORES

22