

# KICHLER®


## Large Landscape Accent



PROJECT:
TYPE:
ORDERING # :
COMMENTS:









## FEATURES

- 7" Accent Light For Wider Light Spread Along Walls, Shrubs & Trees
- Cast Aluminum Housing
- Tempered Convex Glass Lens
- 8" of Usable 200° 18 AWG Wire Leads
- 4000V (4KV) Pulse Rated Medium Base Porcelain Socket
- Max Lamping 175W PAR38 Metal Halide or 150W PAR38 / R40 Incandescent (Not Included)
- Remote Ballast Required for HID Lamping
- ANSI / UL Listed Wet Location
- Housing Includes a 1-Year Warranty From Date of Purchase
- HID Ballasts Include a 2-Year Warranty



## ORDERING INFORMATION

EXAMPLE: 15251AZT (Product # & Finish)

PRODUCT	FINISH	REMOTE BALLAST SPECS	MOUNTING ACCESSORIES	LENS ACCESSORIES
15251	AZT - Textured Architectural Bronze 	<b>Above Ground Ballast</b> <b>15MHS175AZT</b> - Single 175W MH 120V ANSI M57 (Complies w/ EISA 2007) - Dimensions: 6.375" W x 9.5" L x 5.25" D - Stamped Steel w/ Textured Architectural Bronze Thermoset Powder Coat Finis - Copper Wrapped Core & Coil w/ HPF 105° High Heat Capacitor & Long Range Ignitor - Rated For -20° F Starting - 0.5" & 0.75" Trade Size Combination Knockouts For Conduit Entry - Mounting Screws & Anchors Included - UL Listed For US & Canada 	<b>15276BK</b> - A Fast, One-Step Connector - Made of Impact / Corrosion Resistant PVC - 2.250" Inside Diameter to Accomodate Conduits of Different Sizes - Accepts .50 NPSM Thread - Designed For 120V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes. - Built-in Stabilizer Removes Need For Concrete  4.375" 19" 2.25"	<b>15660AZT</b> - PAR38 / R40 Medium Hood - 4.92" in Length <b>15660BKT</b> - PAR38 / R40 Medium Hood - 4.92" in Length  <b>15668AZT</b> - PAR38 / R40 Long Hood - 12" in Length <b>15668BKT</b> - PAR38 / R40 Long Hood - 12" in Length  <b>15625BL</b> - Large Blue Lens Filter - Tempered Glass to Resist Heat & Impact - Enhances Color to Bring Out The True Rich Greens of Foliage 
	BKT - Textured Black 	<b>In Ground Ballast</b> <b>15IGMHS175AZ</b> - Single 175W MH 120V ANSI M57 (Complies w/ EISA 2007) - Dimensions: 9.625" Diameter x 12" Height - Single Piece Polyphenylene (PPS) Glass Reinforced Composite w/ Molded-in Ribs to Prevent Ground Shift - Quick Disconnect Ballast w/ Bracket Handle - 0.5" NPSM Removable Plug For Direct Fixture Mount & Remote Mount Application - Two Threaded 0.75" NPT Entries For Conduit Attachment - Re-Enterable Encapsulant 3M 8882 Potting Compound Included - One Piece, Molded Silicone O-Ring - Captive & Gasketed - CSA Listed For US & Canada  <b>Please Note:</b> Maximum Distance From Lamp to Ballast Cannot Exceed 15 Feet		

## NOTES

For Warranty Information, please visit [www.landscapelighting.com](http://www.landscapelighting.com)

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

